



## **POWDERED SOILTAC®**

### Frequently Asked Questions

<b>Prices</b>	Current Powdered Soiltac® pricing is available upon request.
<b>GSA Schedule</b>	Powdered Soiltac® is available through our Federal GSA contract (#GS07F5364P).
<b>Payment Terms</b>	Prepaid or Net 30 Days upon approved credit.
<b>Payment Method</b>	Cash, Check, Visa, MSTC, AMEX, Letter of Credit, Govt. Cards & Wire Transfer.
<b>Bids / Proposals</b>	Formal bids and proposals are available upon request.
<b>Minimum Order</b>	One 55 pound (25 kg) polypropylene bag (small test samples are available).
<b>Availability</b>	1,000 bags are normally stocked and available on an immediate basis.
<b>Turn-Around</b>	< 48 hours after order is placed and sales terms fulfilled.
<b>Large Volumes</b>	3-14 day turn-around for multiple full truckload or full container shipments.
<b>Production Limits</b>	None. Powdered Soiltac® can be manufactured rapidly in unlimited volumes worldwide.
<b>Prime Material</b>	Powdered Soiltac® is a "Prime" material, not blended or recycled.
<b>By-Products</b>	Powdered Soiltac® is not an ultra-filtrate, by-product, of-spec or off-grade.
<b>Curing</b>	Powdered Soiltac® does not cure chemically; it cures as the water evaporates.
<b>Cure Time</b>	Typically, 24 hours (@70°F/21°C) is normal. Temperature is the primary factor.
<b>Penetration Depth</b>	1/8 <sup>th</sup> to 2" deep for topical applications. Soil type & compaction are the primary factors.
<b>Cold Weather</b>	Will significantly increase cure time. The lower the temperature the longer the cure time.
<b>Freezing</b>	Powdered Soiltac® is unaffected by temperature until dispersed into a liquid emulsion.
<b>Shipping</b>	National & International. Non-Hazardous and Non-Regulated. Worldwide production.
<b>Guarantee</b>	Soilworks® guarantees each batch of Powdered Soiltac® meets the stated specifications.
<b>Normal Life Span</b>	Indefinitely with maintenance. Typically, 12-24 months prior to first maintenance coat.
<b>Shelf Life</b>	Unlimited. If stored in a cool dry place.
<b>Maintenance</b>	Approximately 30% of the original volume used after the first 12-24 months. Cumulative.
<b>Soil Type</b>	Any. Best with non-plastic materials with a well graded grain size distribution and fines.
<b>Rain / Precipitation</b>	Once applied and cured, Powdered Soiltac® is no longer water soluble.
<b>Uncured Cleaning</b>	Rinse equipment immediately. Simply use water to rinse out any uncured product.
<b>Cured Cleaning</b>	Difficult to remove. Use hot water pressure washer with scrub brush and solvents.
<b>Gray Water Dilution</b>	Powdered Soiltac® can be diluted with almost any water including gray water.
<b>Sea Water Dilution</b>	Powdered Soiltac® can be diluted with sea salt water. Do not store over 8 hrs.
<b>Performance Factors</b>	Application rate, soil type, dilution, compaction, traffic, penetration, climate & others.
<b>Harmonized Code</b>	The common International Tariff Code for Powdered Soiltac is 3905.29.00.00.
<b>National Stock No.</b>	U.S. Dept. of Defense Powdered Soiltac NSN: 6850-01-560-5408 (55# / 25kg Bag)

